



## Products:

### **IRON-FACE - FF-400C3-PW®**

*High Strength Laminated Facer Film featuring  
Virtually Zero Stretch and Shrink and Zero Light Transmission*

- 4 mil Coextruded/Cross Linked PE/PP blended Film (will not cross corner curl)
- Tensile strength MD 31 Lb/In-Width ASTM D 882
- Tensile strength TD 30 Lb/In-Width ASTM D 882
- COF .52 - .6 ASTM D 1894
- Tear MD 3,150 grams ASTM D 1922
- Tear TD 3,850 grams ASTM D 1922
- Dart Impact 1620 grams ASTM 1709
- Puncture 38 lbs ASTM E 154
- Density .935 grams/cm<sup>3</sup>
- Corona treated to 40+ dyne/cm<sup>2</sup>
- Opacity 90%
- Thermal shrinkage MD < 7% (5 min 266° air Oven)
- Thermal shrinkage TD < 4% (5 min 266° air Oven)
- Current width capacity 120"
- Standard colors White, Black, Blue with color matching capability (Pantone)
- Printing any color up 4 colors



**Proudly Made in the USA!**

***We Build It Smarter, Stronger...BETTER!***

#### **Colorado Facility**

4699 Nautilus Court, Suite 402 / Boulder, CO 80302  
**p:** 303.530.1748 / **f:** 303.530.1788  
**e:** sales@flatiron-films.com / **w:** flatiron-films.com

#### **Maryland Facility**

9630 Gerwig Lane / Columbia, MD 21046  
**tf:** 877.276.3456 (FILM) / **p:** 410.381.3456 (FILM) / **f:** 410.381.3459  
**e:** info@flatiron-films.com / **w:** flatiron-films.com