



Product Application:

IRON-BARR 10 - Under-Slab Vapor Barrier Membrane

Description:

IRON-BARR 10 Under-Slab Vapor Barrier Membrane is a 10 mil patented multi-ply lamination combining a highly puncture resistant virgin polyolefin film (PP/PE blend), with a 2x-side metalized polyester film. This oriented high-barrier METPET offers superior tensile strength, and unbeatable water vapor barrier properties. The tough blended virgin polyolefin film provides a virtual, puncture proof shield, to protect against the roughest under-slab construction site conditions.

Features:

- Superior Under-Slab or Between-Slab Moisture-Vapor Protection for the life of the building.
- **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** is designed for use in systems, as an excellent barrier/retardant, against soil gases - including radon and methane. Additionally, it provides protection against soil contamination, including oil by-products and sulfates.
- Superior resistance to UV exposure.
- Chemical and rot resistant.

Benefits:

- Can be used in contact with, and directly below, the slab without a Sand Bed or Protection Course.
- Higher yielding rolls, greatly increase daily coverage rates.
- Superior puncture resistance allows for installations over the roughest site conditions.
- **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** will not tear, crack, split or puncture under normal working conditions.
- **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** can be exposed for up to 24 months
- DEVCOM Premium Seam Tape provides superior "Primerless" seam sealing even in cold and wet conditions.
- Specified Primers, Mastic and Detail Tapes, are used to seal the UNDER-SLAB VAPOR BARRIER Membrane at penetrations, and concrete surfaces, to provide you a COMPLETELY SEAMLESS, VAPOR BARRIER PACKAGE.

IRON-BARR 10 Physical Properties:

Properties	Test Standard	Results
Total Thickness (in)		10 mils
Yield		4,917 sq in/lb
Under-Slab Vapor Barrier	ASTM E1745 (Class A, B & C)	Exceeds All Standards
Tensile Strength	ASTM D882	82 lbs
Puncture Resistance	ASTM D1709 (Method B)	3,640 grams
Water Vapor Permeance	ASTM E96 (Method A)	.0029
Chemical Resistance	ASTM E154	Unaffected
Life Expectancy	ASTM E154	Indefinite
Seam Tape Adhesion (cohesion)	ASTM D1876	7 lb per lineal in



Storage & Handling:

Store all materials above ground. Do not store products in direct sunlight. Do not remove Seam Tape from box until ready to use. For cold weather applications, store Seam Tape in a heated airspace at a temperature of 50 degrees F (10 degrees C) or higher for at least 2 days prior to application. Remove only the material that can be applied within 2 hours. Store all materials away from open flames or sparks.

Application:

ASTM E 1643-98 is an installation guide titled, "Standard Practice for Installation of Water Vapor Retarders Used in Contact with Earth or Granular Fill Under Concrete Slabs." Flatiron Films LLC subscribes to all of the installation procedures outlined in this standard. Installation of **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** shall be in accordance with this standard.

Under-Slab Installation Instructions:

1. **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** can be installed over aggregate, sand or tamped earth base, a sand base is not necessary, the **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** is strong enough to withstand the toughest construction environments without a protection course.
2. Unroll **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** over the entire area parallel with the direction that the concrete slab is to be poured. Side and end laps should be overlapped six inches and sealed using 4" wide DEVCOM Premium Seam Tape.
3. The **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** must be sealed near the top of the vertical surface of the footing and the entire perimeter of the slab area using either DEVCOM Premium Seam Tape or a combination of DEVCOM and one of the alternate products listed later.
4. All penetrations must be sealed including all structural, plumbing, electrical and miscellaneous penetrations must be sealed using DEVCOM Premium Seam Tape, or one of the alternate products listed later.
5. If the **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** is damaged during or after installation, cut a piece of **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** large enough to cover the damage by six inches in all directions, clean the membrane of all dust, dirt and moisture and seal with DEVCOM Premium Seam Tape.
6. Once installed and completely sealed, the **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** is ready for pouring concrete; the strength of the UNDER-SLAB VAPOR BARRIER Membrane System is such that a sand or gravel protection course over the membrane is not required.

Vertical Wall Installation Instructions *(for use as a protection course)*

1. Install an approved waterproofing membrane according to the manufacturer's installation instructions.
2. While the membrane is still tacky, install **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** as a protective course over the applied waterproofing membrane, Side and end laps should be overlapped six inches and sealed using 4" wide DEVCOM Premium Seam Tape.
3. A properly installed termination bar mechanically fastened to the wall at the top termination of the waterproofing membrane is required.
4. Care must be taken when back filling against the material so that it is not damaged or punctured; if damage occurs to the **IRON-BARR 10 Under-Slab Vapor Barrier Membrane**, cut a piece of **IRON-BARR 10 Under-Slab Vapor Barrier Membrane** large enough to cover the damage by six inches in all directions, clean the membrane of all dust, dirt and moisture and seal with DEVCOM Premium Seam Tape.



Limitations:

The preceding installation instructions are very general installation instructions. Instructions on architectural or structural drawings should be reviewed & followed. ASTM Standard E1643 "Standard Practice for Installation of Water Vapor Retarders Used in Contact with Earth or Granular Fill Under Concrete Slabs" also provides valuable installation and design information.

Warranty:

Flatiron Films LLC warrants materials to be free of defects in manufacturing for a period of 1-Year from date of purchase and will replace or, at our option, refund the purchase price any materials proven to be defective. THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTY GUARANTEE EXPRESSED OR IMPLIED, INCLUDING: WARRANTIES OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. IN NO EVENT WILL FLATIRON FILMS LLC BE LIABLE FOR INCIDENTAL CONSEQUENTIAL DAMAGES NOR SHALL LIABILITY, IF ANY, EXTEND BEYOND THE PURCHASE PRICE OF MATERIAL. FLATIRON FILMS LLC DOES NOT WARRANT THE WORKMANSHIP OF THE APPLICATOR.

Alternate Specified Products:

Protecto Wrap Super Stick Seam Tape
Protecto Wrap #500 Detail Tape
Protecto Wrap #160H Mastic
Protecto Wrap Jiffy Seal 140/60
Protecto Wrap CMU 100 applied by roller, brush or spray.
Protecto-Tak Primer
Protecto Wrap #100 Primer

We Build It Smarter, Stronger...BETTER!

Colorado Facility

4699 Nautilus Court, Suite 402 / Boulder, CO 80302
p: 303.530.1748 / **f:** 303.530.1788
e: sales@flatiron-films.com / **w:** flatiron-films.com

Maryland Facility

9630 Gerwig Lane / Columbia, MD 21046
tf: 877.276.3456 (FILM) / **p:** 410.381.3456 (FILM) / **f:** 410.381.3459
e: info@flatiron-films.com / **w:** flatiron-films.com